



Attero Tech by QSC

unDX2IO+

Dante/AES67 network audio
Wall Plate - 4x2 mic/line I/O

Features


- Dante Domain Manager™ ready
- Small form factor allows for easy co-location near analog sources or sinks
- 802.3af compliant PoE powered
- Four input gains to accommodate common line levels, dynamic and phantom powered mics
- +48V phantom power per channel
- Analog output gain is software adjustable between 0 dB and -60 dB plus mute to accommodate all types of line input audio equipment - both consumer and professional levels
- Industry standard +20 dBu maximum input levels (at 0 dB input gain) and +20 dBu maximum output levels
- Product accessory kit available



Applications: Hotel Ballrooms • Spas • Fitness Facilities Convention Centers • Education • Conference Center

The unDX2IO+ is a cost-effective multi-IO Dante™ audio network wall plate. The unDX2IO+ features two balanced mic/line XLR inputs, two balanced XLR line outputs, and two balanced line inputs on depluggable connectors on the side of the unit. All inputs and outputs can be used simultaneously and all audio channels are available separately. The unDX2IO+ is designed to fit into all dual-gang US junction boxes, mud rings, and old work brackets. The unDX2IO+ is PoE enabled, so all connectivity (power, control, and data) is provided by a single CAT-5/6 cable. The wall plate's size and I/O density make it easy to put Dante connectivity wherever it's needed.

Dimensions:



unDX2IO+ Details

Audio Inputs		Dante Network	
Input types	3-pin XLR (balanced and RF filtered)	Physical level	Standard ethernet
Gain	-18 dB, -3dB, +25dB, +40dB, software selectable	Connector	Single RJ-45
Input impedance	>1.8 K Ω at any gain setting	Cable quality	CAT-5e or better
Maximum input levels: 1 & 2	+20 dBu @ 0 dB w/ -15 dB Pad +5 dBu @ 0 dB gain, -22 dBu @ +25 dB gain, -38 dBu @ +40 dB gain	Transmission speed	100 Mbps
Maximum input levels: 3 & 4	+4 dBu Mode: +20 dBu -10 dBV Mode: +12 dBu	Supported sample rates	44.1 kHz, 48 kHz
Phantom power	+48v, software selectable	Minimum Dante network latency	1 ms
Audio Outputs		General	
Output type	Balanced line level with automatic muting on loss of Dante signal	Dimensions (HWD)	4.2 x 3.5 x 2 in (114.3 x 88.9 x 50.8 mm)
Output gain	0 dB	Weight	0.6 lb (.27 kg)
Maximum output level	+20 dBu	Operating temperature	0 to 40° C
Audio Performance		Regulatory compliance	FCC CFR 47 Parts 15B Class A ICES-003 CE (EN55022) RoHS REACH
EIN	-115 dBu (+40 dB gain)	Environmental	
THD+N	< -85 dBu @ 0 dB gain	PoE	802.3af PoE PD compliant
Frequency response	< 0.05% at any gain, input signal 3 dB below maximum	Power consumption	< 5 W max



1675 MacArthur Boulevard • Costa Mesa, CA 92626 • Ph: 800/854-4079 or 714/957-7100 • Fax: 714/754-6174

© 2019 QSC, LLC all rights reserved. QSC and the QSC logo are registered trademarks of QSC, LLC in the U.S. Patent and Trademark office and other countries. All other trademarks are the property of their respective owners. Patents may apply or be pending.

unDX2IO+ Spec Sheet 12/13/2019

